

# LL3-DT03

LL3

FIBERS

**SICK**  
Sensor Intelligence.



## Ordering information

Type	Part no.
LL3-DT03	5308072

**Included in delivery:** BF-WLL160-10 (1), FC (1)

Other models and accessories → [www.sick.com/LL3](http://www.sick.com/LL3)

## Detailed technical data

### Features

<b>Device type</b>	Fibers
<b>Functional principle</b>	Proximity system
<b>For fiber-optic sensor</b>	GLL170(T), WLL180T, WLL80
<b>Fiber length</b>	2,000 mm
<b>Fiber material</b>	Polymethylmethacrylat (PMMA)
<b>Jacket material</b>	Polyethylen (PE)
<b>Fiber head material</b>	Stainless steel <sup>1)</sup>
<b>Outer diameter, fiber-optic cable connection</b>	1 mm
<b>Fiber-optic cable cuttable</b>	✓
<b>Smooth sleeve diameter (greatest diameter)</b>	2.5 mm
<b>Fiber-optic head design</b>	Smooth sleeve
<b>Fiber arrangement</b>	Monofiber
<b>Core structure</b>	2 x Ø 0,5 mm <sup>2)</sup> Monofiber
<b>Angle of dispersion &lt; 60°</b>	No
<b>Compatibility with infrared light (1,450 nm)</b>	No
<b>Highly flexible/elastic fibers (bend radius 1–4 mm)</b>	No
<b>Adapter end sleeves required</b>	Yes
<b>Angle of dispersion</b>	60°
<b>Integrated lens</b>	No
<b>Minimal object diameter</b>	0.015 mm <sup>3)</sup>
<b>Included with delivery</b>	Adapter sleeves, BF-WLL160-10 (1.0 mm) adapter sleeves, FC fiber cutter (5304141)
<b>Compatibility tip adapters</b>	No
<b>Special features</b>	Standard, super-compact head and end sleeve, large sensing range

<sup>1)</sup> Stainless steel.

<sup>2)</sup> C = Coaxial, S = Sender, E = Receiver.

<sup>3)</sup> Minimum detectable object was determined at optimum measuring distance and optimum setting.

### Mechanics/electronics

<b>Bend radius, fibre-optic cable</b>	15 mm
<b>Ambient operating temperature</b>	-40 °C ... +70 °C

## Classifications

<b>ECl@ss 5.0</b>	27270905
<b>ECl@ss 5.1.4</b>	27270905
<b>ECl@ss 6.0</b>	27270905
<b>ECl@ss 6.2</b>	27270905
<b>ECl@ss 7.0</b>	27270905
<b>ECl@ss 8.0</b>	27270905
<b>ECl@ss 8.1</b>	27270905
<b>ECl@ss 9.0</b>	27270905
<b>ECl@ss 10.0</b>	27270905
<b>ECl@ss 11.0</b>	27270905
<b>ECl@ss 12.0</b>	27270905
<b>ETIM 5.0</b>	EC002651
<b>ETIM 6.0</b>	EC002651
<b>ETIM 7.0</b>	EC002651
<b>ETIM 8.0</b>	EC002651
<b>UNSPSC 16.0901</b>	39121528

## Sensing ranges with WLL80

<b>Operating mode 16 <math>\mu</math>s</b>	35 mm
<b>Operating mode 70 <math>\mu</math>s</b>	110 mm
<b>Operating mode 250 <math>\mu</math>s</b>	175 mm
<b>Operating mode 500 <math>\mu</math>s</b>	215 mm
<b>Operating mode 1 ms</b>	250 mm
<b>Operating mode 2 ms</b>	360 mm
<b>Operating mode 8 ms</b>	580 mm

## Sensing ranges with WLL180T

<b>Operating mode 16 <math>\mu</math>s</b>	18 mm
<b>Operating mode 70 <math>\mu</math>s</b>	55 mm
<b>Operating mode 250 <math>\mu</math>s</b>	95 mm
<b>Operating mode 2 ms</b>	190 mm
<b>Operating mode 8 ms</b>	360 mm
<b>Note</b>	Sensing ranges referring to fiber-optic sensors with type of light: visible red light

## Sensing ranges with GLL170


<b>Operating mode 250 <math>\mu</math>s</b>	60 mm
---	-------

## Sensing ranges with GLL170T

<b>Operating mode 50 <math>\mu</math>s</b>	50 mm
<b>Operating mode 250 <math>\mu</math>s</b>	90 mm

### Dimensional drawing (Dimensions in mm (inch))

LL3-DT03



## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)