

PE – White Insulation

Type A Set – White
Standard Plain End Line



Type B Set – White
Mini-Split Twin Tube (Joined)



Type C Set – White
Mini-Split (Separate)



Type D Set – White
Insulated Copper Tube (Single Line)



Type E Set – White
Plain End Fully Assembled (Taped)



Type E Set – White with Thermostat Wire
Standard Plain End Line



PE – Black Insulation

Type A Set – Black
Standard Plain End Line



Type B Set – Black
Mini-Split Twin Tube (Joined)



Type C Set – Black
Mini-Split (Separate)



Type D Set – Black
Insulated Copper Tube (Single Line)



Type E Set – Black
Plain End Fully Assembled (Taped)



Black Rubber Insulation

Type F Set

Standard Plain End Line



Type G Set

Mini-Split (Separate)



Type H Piece

Insulated Copper Tube (Single Line)



Type I Set

Plain End Fully Assembled (Taped)



Type I Set – Black with Thermostat Wire

Plain End Fully Assembled (Taped)



Cool Pull Mini Line Set Kits

ICOOL split line set kits consist of annealed copper tube with a high quality insulation layer (M1 certified) widely used for the insulation of split air conditioners and refrigerant equipment.

Copper tubes are produced according to ASTM B 280 or B743 with the temper of soft annealed. All kits are suitable for R410a refrigerant and other high-pressure refrigerant.

Insulation layer is made of cross-lined foam polyethylene with closed cells. The insulation is covered with embossed polyethylene film to prevent the foam from creasing.

Fire retardant and UV resistance
 Heating conduction at 0°C, ≤ 0.033 W/mk
 Average Density: 33KG/m³
 Working temperature from -40°F to +300°F
 Vapor resistance: $\mu > 5000$
 White/external non-toxic and resistant to external chemical agents and ultra-violet rays.

Mini Split Line Set Accessories

Accessories consist of all components needed for air conditioner installation.

1. Drain pipe
2. Non-adhesive PVC tape
3. Electrical wire (TC-ER 4/16 AW / 4/14 AWG)
4. Mud (150g or 200g can be selected)
5. Wall sleeve kits (PVC sleeve cap)

Packing

COPPER TUBE SIZE	AIR CONDITIONER CAPACITIES
1/4" and 3/8"	9000 BTU
1/4" and 1/2"	12000 BTU and 18000 BTU
1/4" and 5/8"	24000 BTU and 28000 BTU
3/8" and 5/8"	36000 BTU inverter

*Standard lengths:

50 ft and 100 ft

*Customized lengths:

10 ft to 164 ft

